

Specifications

Page 3 of 7 Pages

I	Curb & Gutter	6310	L.F.	
J	Stone Stabilization	5800	Tons	
K	Base Paving - Type B	1956	Tons	
L	Top Paving - Type C	1139	Tons	
M	Replace Topsoil - On site (6" depth)	8960	C.Y.	
N	Seed & Mulch	35443	S.Y.	
O	Inlet Protection	21	Each	
P	Rip Rap	183.75	Tons	
TOTAL PHASE I-SITWORK AND SEDIMENT & EROSION CONTROL				\$ 831,337.00
 6 PHASE I - STORMWATER MANAGEMENT				
A	14 x 23 ERCP Drainage	803	L.F.	
B	Inlets	21	Each	
C	Box Culvert	1	Each	
TOTAL PHASE I - STORMWATER MANAGEMENT				\$ 175,890.00
 7 PHASE 1 - SANITARY SEWER				
A	Sewer Testing	3376	L.F.	
B	Sewer Cleanup	3376	L.F.	
C	Sewer Manhole	17	Each	
D	8" PVC Sewer Main	1413	L.F.	
E	10" PVC Sewer Main	868	L.F.	
F	12" PVC Sewer Main	1095	L.F.	
G	6" Sewer Laterals	1002	L.F.	
H	6" Sewer Cleanouts	63	Each	
I	Lift Station Dewatering	1	Lump Sum	
J	Lift Station	1	Each	
TOTAL PHASE I - SANITARY SEWER				\$ 508,633.00
 8 PHASE I - WATER DISTRIBUTION				
A	Water Testing	3431	L.F.	
B	Restoration (Trench Repair For Tie In To Existing Water Main)	1	Lump Sum	
C	Water Cleanup	3431	L.F.	
D	8" C-900 Water Main	3431	L.F.	

This page becomes part of and in conformance with proposal for:
Bunting and Murray Construction Corporation

Submitted by: scm Date: 3/21/08

Signature _____
Date of Acceptance _____